



ACCELERATOR FOR ACRYLIC PRODUCTS

Product intended for professional use.

PRODUCT RANGE:

43 294 Accelerator for acrylic products 150 mL

CHARACTERISTICS:

An effective agent designed for use as an additive to shorten the drying time of solvent-based two-component acrylic products. It optimizes the coat hardening process during application of the varnish material in adverse weather conditions such as low ambient temperature and/or high humidity. The use of the accelerator is also recommended where a reduced standard drying time of 2K products such as primers, acrylic paints and varnishes is required.

PHYSICAL AND CHEMICAL PROPERTIES:

Colourless liquid with a sweet, slightly aromatic smell.

APPLICATIONS:

Two-component acrylic products (varnishes, paints and primers).

METHOD OF USE:

SAMPLE SYSTEM:

AMOUNT OF READY-TO-USE 2K MIXTURE	RECOMMENDED AMOUNT OF ACCELERATOR	
	1%	2%
100 mL	1.0 mL	2.0 mL
150 mL	1.5 mL	3.0 mL
300 m	3.0 mL	6.0 mL
500 mL	5.0 mL	10.0 mL

NOTE:

Do not exceed the recommended amounts of the accelerator. Do not use with FAST-type hardeners or fast paint systems.

The use of more than the recommended amount of the accelerator may cause paint coat defects such as pinholing, solvent pop, orange peel, peeling, matting, etc.

The use of the accelerator shortens the pot life of the mixture.

Do not use at high ambient temperatures.



CLEANING THE EQUIPMENT:

POLFILL NITRO Thinner.

STORAGE:

Store in original, tightly closed containers, in a dry, well-ventilated place, away from sources of heat and ignition, at a temperature from 5°C to 25°C. Do not expose to direct sunlight.

WARRANTY PERIOD:

The warranty period is given on the product label.

HEALTH & SAFETY RECOMMENDATIONS:

Product safety data sheet and applicable health and safety regulations for working with chemical agents.

The information contained in this sheet has been developed based on our knowledge and practice. However, no individual product properties can be guaranteed under different conditions of use beyond our control. Therefore, we cannot accept full responsibility for the results obtained in specific conditions of use. It is necessary to test the application of the product on a small area, due to the potential differences in the product performance depending on the substrate on which it is applied. We guarantee proper quality when used in accordance with the instructions contained in this Technical Data Sheet.