



## FADE OUT THINNER

*Product intended for professional use.*

### PRODUCT RANGE:

43 174	Fade Out Thinner 500 mL
43 175	Fade Out Thinner 1 L

### CHARACTERISTICS:

Thinner for use in local repairs to fade out optical differences in gloss between the old and new paint coats. The use of the product effectively improves the appearance of the transition area, which guarantees a perfectly looking repair. It works well with commercially available 2K clearcoats and acrylic enamel topcoats.

### PHYSICAL AND CHEMICAL PROPERTIES:

Colourless liquid with an aromatic, sweet smell.

### APPLICATIONS:

- Transition zones in local repairs.

### METHOD OF USE:

Matte the intended contact zone between a new coat and the old coating with P1200 – P1500 abrasive paper, then thoroughly wash the area with Polfill Silicone Remover AUTOMOTIVE or PRO.

Apply Fade Out Thinner to the contact zone between the new coat and the old coating using a spray gun with a 0.8 – 1.2 mm nozzle at a pressure equal to or lower than that recommended by the equipment manufacturer.

The best results can be obtained by applying the thinner after each applied paint or varnish coat. Otherwise, the thinner should be used immediately after the final coat has been applied.

### STORAGE:

Store in original, tightly closed containers, in a dry, cool place, away from sources of heat and ignition, at a temperature from 5 to 20°C. Do not expose to direct moisture or sunlight.

### WARRANTY PERIOD:

The warranty period is given on the product label.



## HEALTH & SAFETY RECOMMENDATIONS:

Product safety data sheet and applicable health and safety regulations for working with chemical agents.

*The information contained in this sheet has been developed based on our knowledge and practice. However, no individual product properties can be guaranteed under different conditions of use beyond our control. Therefore, we cannot accept full responsibility for the results obtained in specific conditions of use. It is necessary to test the application of the product on a small area, due to the potential differences in the product performance depending on the substrate on which it is applied. We guarantee proper quality when used in accordance with the instructions contained in this Technical Data Sheet.*

### LERG SA

Pustków-Osiedle 59d  
39-206 Pustków 3  
Poland

### CUSTOMER SERVICE

tel.: +48 (14) 680 62 85  
e-mail: polfill@lerg.pl  
www.polfill.pl

Date: 14/03/2023

Rev. 3