



HARDENER EXPRESS 1:2

Product intended for professional use.

PRODUCT RANGE:

43 313	Acrylic clearcoat EXPRESS 2K 2 : 1; 500 mL
43 216	Hardener EXPRESS 1 : 2; 250 mL
43 314	Acrylic clearcoat EXPRESS 2K 2 : 1; 1 L
43 317	Hardener EXPRESS 1 : 2; 500 mL
43 315	Acrylic clearcoat EXPRESS 2K 2 : 1; 5 L
43 246	Hardener EXPRESS 1 : 2; 2.5 L
43 146	Thinner for acrylic products 500 mL
43 352	Thinner for acrylic products 1 L
43 230	Thinner for acrylic products 5 L

CHARACTERISTICS:

The hardener used for curing Acrylic clearcoat EXPRESS 2K 2:1 is a mixture of isocyanate resins and organic solvents. It is designed to provide a perfect look of the paint shell whilst ensuring a fast cure to significantly reduce the time required for paint work.

PHYSICAL AND CHEMICAL PROPERTIES:

Colourless liquid with an aromatic, sweet smell.

APPLICATIONS

MIXING PROPORTIONS:

Mix thoroughly 1 part by volume of hardener with 2-4 parts by volume of the coat until a uniform consistency.

APPLICATION CONDITIONS:

Minimum working temperature	8°C
Maximum working temperature	28°C
Maximum relative humidity	75%

CLEANING THE EQUIPMENT:


Clean the equipment immediately after work.

POLFILL Thinner for acrylic products.

POLFILL NITRO thinner.



STORAGE:



Store in original, tightly closed containers, in a dry, cool place, away from sources of heat and ignition, at a temperature 5 to 20°C. Do not expose to direct sunlight. Protect from moisture and freezing.

GUARANTEE PERIOD:

The warranty period is given on the product label.

HEALTH & SAFETY RECOMMENDATIONS:

Product safety data sheet and applicable health and safety regulations for working with chemical agents.

The information contained in this sheet has been developed based on our knowledge and practice. However, no individual product properties can be guaranteed under different conditions of use beyond our control. Therefore, we cannot accept full responsibility for the results obtained in specific conditions of use. It is necessary to test the application of the product on a small area, due to the potential differences in the product performance depending on the substrate on which it is applied. We guarantee proper quality when used in accordance with the instructions contained in this Technical Data Sheet.