

HARDENER RACER EVOLUTION 1:2

Product intended for professional use.

PRODUCT RANGE:

43 385	Acrylic clearcoat RACER Evolution 2K HS 2:1, 500 mL
43 388	Hardener RACER Evolution 1:2, 250 mL
43 386	Acrylic clearcoat RACER Evolution 2K HS 2:1, 1 L
43 389	Hardener RACER Evolution 1:2, 500 mL

CHARACTERISTICS:

The hardener used for curing Acrylic clearcoat RACER Evolution 2K HS 2:1 is a mixture of isocyanate resins and organic solvents. It is designed to provide a perfect look of the paint shell whilst ensuring a fast cure to significantly reduce the time required for paint work.

PHYSICAL AND CHEMICAL PROPERTIES:

Colourless liquid with an aromatic, sweet smell.

APPLICATIONS:

MIXING PROPORTIONS:

Add the hardener to the clearcoat in the appropriate ratio (by volume): 1 part of the hardener to 2 parts of the clearcoat. Mix thoroughly until a homogeneous consistency.

APPLICATION CONDITIONS:

Use at temperatures from 8°C to 28°C and relative humidity ≤ 75%.


CLEANING THE EQUIPMENT:

Clean the equipment immediately after work, using:

POLFILL NITRO thinner
POLFILL thinner for acrylic products



STORAGE:



Store in original, tightly closed containers, in a dry, cool place, away from sources of heat and ignition, at a temperature 5 to 25°C. Do not expose to direct sunlight. Protect from moisture and freezing.

WARRANTY PERIOD:

The warranty period is given on the product label.

HEALTH & SAFETY RECOMMENDATIONS:

Product safety data sheet and applicable health and safety regulations for working with chemical agents.

The information contained in this sheet has been developed based on our knowledge and practice. However, no individual product properties can be guaranteed under different conditions of use beyond our control. Therefore, we cannot accept full responsibility for the results obtained in specific conditions of use. It is necessary to test the application of the product on a small area, due to the potential differences in the product performance depending on the substrate on which it is applied. We guarantee proper quality when used in accordance with the instructions contained in this Technical Data Sheet.