

SILICONE REMOVER PRO

Product intended for professional use.

PRODUCT RANGE:

43 178	Silicone Remover PRO 1 L
43 179	Silicone Remover PRO 5 L

CHARACTERISTICS:

A high-performance, powerful agent for cleaning and degreasing surfaces. It easily removes silicone compounds, fats, oils, waxes and asphalts. It is very effective in removing residues of stickers, foils and adhesive tapes. Perfect for both industrial and car paintwork applications. An extended flash-off time boosts the product's performance and makes easy the application on large surfaces. Polfill PRO remover can be also successfully used as a cleaning agent on metal engine parts, transmission parts, tools, etc.

PHYSICAL AND CHEMICAL PROPERTIES:

Colourless liquid with a characteristic, aromatic smell. Maximum volatile organic compounds content in ready-to-use product: < 850 g/L.

APPLICATIONS

SUBSTRATE:

- steel,
- galvanized steel,
- stainless steel,
- aluminium,
- plastics,
- cured primer paints,
- cured varnish coatings,
- polyester putties
- polyester laminates,
- glass surfaces.

Note: the product may dissolve 1K and other under-cured coatings; to avoid this, it is recommended to use Polfill Automotive Remover.

METHOD OF USE:

Apply the Silicone remover onto the surface using a pressure sprayer or a suitable cleaning cloth. Using a paper towel, for example, wash the surface thoroughly and then wipe it dry. For heavily soiled surfaces, repeat the operation. It is not recommended to leave the remover on the surface to evaporate freely.



STORAGE:

Store in original, tightly closed containers, in a dry, cool place, away from sources of heat and ignition, at a temperature 5 to 20°C. Do not expose to direct moisture and sunlight.

WARRANTY PERIOD:

The warranty period is given on the product label.

HEALTH & SAFETY RECOMMENDATIONS:

Product safety data sheet and applicable health and safety regulations for working with chemical agents.

The information contained in this sheet has been developed based on our knowledge and practice. However, no individual product properties can be guaranteed under different conditions of use beyond our control. Therefore, we cannot accept full responsibility for the results obtained in specific conditions of use. It is necessary to test the application of the product on a small area, due to the potential differences in the product performance depending on the substrate on which it is applied. We guarantee proper quality when used in accordance with the instructions contained in this Technical Data Sheet.